

## SOLID SOD NOTES

- FINE GRADE AREAS TO ACHIEVE FINAL CONTOURS INDICATED. LEAVE AREAS TO RECEIVE TOPSOIL 3" BELOW FINAL DESIRED GRADE IN PLANTING AREAS AND 1" BELOW FINAL GRADE IN TURF
- ADJUST CONTOURS TO ACHIEVE POSITIVE DRAINAGE AWAY FROM BUILDINGS, PROVIDE UNIFORM ROUNDING AT TOP AND BOTTOM OF SLOPES AND OTHER BREAKS IN GRADE, CORRECT IRREGULARITIES AND AREAS WHERE WATER MAY STAND,
- ALL LAWN AREAS TO RECEIVE SOLID SOD SHALL BE LEFT IN A MAXIMUM OF 1'BELOW FINAL FINISH GRADE, CONTRACTOR TO COORDINATE OPERATIONS WITH ON-SITE CONSTRUCTION MANAGER.
- CONTRACTOR TO COORDINATE WITH ON-SITE CONSTRUCTION MANAGER FOR AVAILABILITY OF EXISTING TOPSOIL.
- PLANT SOD BY HAND TO COVER INDICATED AREA COMPLETELY. INSURE EDGES OF SOD ARE TOUCHING. TOP DRESS JOINTS BY HAND WITH TOPSOIL TO FILL VOIDS.
- ROLL GRASS AREAS TO ACHIEVE A SMOOTH, EVEN SURFACE, FREE FROM UNNATURAL UNDULATIONS.
- WATER SOD THOROUGHLY AS SOD OPERATION PROGRESSES.
- CONTRACTOR SHALL MAINTAIN ALL LAWN AREAS UNTIL FINAL CONTRACTOR SHALL MAINTAIN ALL JAWN AREAS ON INTERTIAL ACCEPTANCE. THIS SHALL INCLUDE, BUT NOT LIMITED TO: MOWING, WATERING, WEEDING, CULTIVATING, CLEANING AND REPLACING DEAD OR BARE AREAS TO KEEP PLANTS IN A VIGOROUS, HEALTHY CONDITION.
- CONTRACTOR SHALL GUARANTEE ESTABLISHMENT OF AN ACCEPTABLE TURF AREA AND SHALL PROVIDE REPLACEMENT FROM LOCAL SUPPLY IF NECESSARY,
- 10. IF INSTALLATION OCCURS BETWEEN SEPTEMBER 1 AND MARCH 1, ALL SOD AREAS TO BE OVER-SEEDED WITH WINTER RYEGRASS, AT A RATE OF (4) POUNDS PER ONE THOUSAND (1000) SQUARE FEET.

## LANDSCAPE TABULATIONS

ALL PLANTING BEDS AND LAWN AREAS TO BE SEPARATED BY STEEL EDGING, NO STEEL TO BE INSTALLED ADJACENT TO SIDEWALKS OR

ALL LANDSCAPE AREAS TO BE 100% IRRIGATED WITH AN UNDERGROUND AUTOMATIC IRRIGATION SYSTEM AND SHALL INCLUDE RAIN AND FREEZE SENSORS,

CONTRACTOR TO PROVIDE A MINIMUM 2% SLOPE AWAY FROM ALL STRUCTURES.

ALL LAWN AREAS TO BE SOLID SOD BERMUDAGRASS, UNLESS OTHERWISE NOTED ON THE DRAWINGS.

GENERAL LAWN NOTES

LOT 14

LOT 15

A.U.D.E. BY SEPARATE INSTRUMENT

0.8.7.5.3. 0.8.7.5.3. 0.8.7.5.3.

-VARIABLE WIDTH ACCESS ESMT

50'x 36' ACCESS EASEMEN' CAB. A, SL. 1316 P.R.C.C.T.

CITY OF NORTH RICHLAND INST. No. D212317659 0.P.R.C.G.T.

Q

SNOW WIDE RICHT-OF-WAY)

E €

RUF

SC SC

F.A.U.D.E. BY-SEPARATE

INSTRUMENT

SOLID SOD BERMUDA GRASS TYPICAL FOR ALL TURF AREAS

(I)

1 89 58 35" W 144.67'

\_\_SOLID SOD BERMUDA GRASS TYPICAL FOR ALL TURF AREAS

S 89\*58'34" E - 160.08'

11 NRS

25 LOR

SEPARATE INSTRUMENT FINE GRADE AREAS TO ACHIEVE FINAL CONTOURS INDICATED ON CIVIL PLANS.

ADJUST CONTOURS TO ACHEVE POSITIVE DRAINAGE AWAY FROM BUILDINGS. PROVIDE UNIFORM ROUNDING AT TOP AND BOTTOM OF SLOPES AND OTHER BREAKS IN GRADE. CORRECT IRREGULARITIES AND AREAS WHERE WATER IMAY STAND.

ALL LAWN AREAS TO RECEIVE SOLID SOD SHALL BE LEFT IN A MAXIMUM OF 1" BELOW FINAL FINISH GRADE, CONTRACTOR TO COORDINATE OPERATIONS WITH ON-SITE CONSTRUCTION MANAGER,

ALL LAWN AREAS TO BE FINE GRADED, IRRIGATION TRENCHES COMPLETELY SETTLED, AND FINISH GRADE APPROVED BY THE OWNER'S CONSTRUCTION MANAGER OR ARCHITECT PRIOR TO INSTALLATION.

CONTRACTOR SHALL PROVIDE (1") ONE INCH OF IMPORTED TOPSOIL ON

ALL ROCKS 3/4" DIAMETER AND LARGER, DIRT CLODS, STICKS, CONCRETE SPOILS, ETC. SHALL BE REMOVED PRIOR TO PLACING TOPSOIL AND ANY LAWN INSTALLATION

CONTRACTOR SHALL VERIFY ALL EXISTING AND PROPOSED SITE ELEMENTS AND NOTIFY ARCHITECT OF ANY DISCREPANCIES, SURVEY DATA OF EXISTING CONDITIONS WAS SUPPLIED BY OTHERS,

2. CONTRACTOR SHALL LOCATE ALL EXISTING UNDERGROUND UTILITIES AND NOTIFY ARCHITECT OF ANY CONFLICTS.
CONTRACTOR SHALL EXERCISE CAUTION WHEN WORKING IN THE

VICINITY OF UNDERGROUND UTILITIES. CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL REQUIRED LANDSCAPE AND IRRIGATION PERMITS.

ALL AREAS TO RECEIVE LAWN.

LANDSCAPE NOTES

PLANT MATERIAL SCHEDULE

Requirement: 15% of site to be landscape area Site= 26,136.80 s.f.

3,920.52 s.f. (15%) 7,221 s.f. (24.5%)

Street Trees requirement: 1 tree required for each 50 Lf. of street

frontage.

10 shrubs for each 50 l.f. of street frontage

Rufe Snow Dr. - 125 l.f.

Provided 3 trees, 3" cal. 39 shrubs 25 shrubs

Parking lot screen- 20" height evergreen hedge provide

Parking lot landscape: 26 parking spaces Requirement: 1 tree per 20 parking spaces

Large Shrub screening for residential adjacency moved due to Mobile

TREES					
TYPE	QTY	COMMON NAME	BOTANICAL NAME	SIZE	REMARKS
LO	7	Live Oak	Quercus virginiana	3" cal.	container, 12' ht., 5' spread, 5' clear straight trur
CE	3	Cedar Elm	Ulmus crassifolia	3" cal.	container, 12' ht., 5' spread min., 5' straight trun
СМ	5	Crepe Myrtle	Lagerstroemia indica	3" cal.	container, 8' ht., 3- trunks, tree form
SHRUBS					
TYPE	QTY	COMMON NAME	BOTANICAL NAME	SIZE	REMARKS
NPH NRS LOR	128 12 29	Needlepoint Holly Nellie R. Stevens Loropetalum	Ilex x cornuta 'Needlepoint' Ilex x 'Nellie R. Stevens' Loropetalum chinensis	5 gal. 45 gal. 3 gal.	container, 24" ht., 20" spread container, 72" ht., 60" spread container grown, 24" ht., 20" spread
GROUND	COVERS				
TYPE	QTY	COMMON NAME	BOTANICAL NAME	SIZE	REMARKS
LIR SC	75 20	Liriope 'Super Blue' Seasonal Color '419' Bermudagrass	Liriope muscari 'Super Blue'  Cynodon dactylon '419'	4" pots 4" pots	container full, 10" o.c. selection by owners, 12" o.c. Solid Sod refer to notes
		-	_		1

NOTE: Plant list is an aid to bidders only. Contractor shall verify all quantities on plan. All heights and spreads are minimums. All plant material shall meet or exceed remarks as indicated. All trees to have straight trunks and be matching within varieties.

RUFE SNOW DR. CITY OF NORTH RICHLAND HILLS, TEXAS STRICKLAND

BROTHER

ISSUE: CITY COMMENTS 09.28.2022 CITY COMMENTS 10.25.2022 CITY COMMENTS 12.16.2022

> DATE: 12.16.2022

SHEET NAME: LANDSCAPE PLAN

SHEET NUMBER:

#### SECTION 02900 - LANDSCAPE

### PART 1 - GENERAL

PART 3 - EXECUTION

3.1 BED PREPARATION & FERTILIZATION

### 1.1 REFERENCED DOCUMENTS

Refer to bidding requirements, special provisions, and schedules for additional require

Work included: Furnish all supervision, labor, materials, services, equipment and appliances required to complete the work covered in conjunction with the landscaping covered in these specifications and landscaping plans, including:

- Planting (trees, shrubs, and grass) Bed preparation and fertilization
- urces tenance until final acceptance

## REFERENCE STANDARDS

- Texas Association of Nurserymen, Grades and Standards

- The Contractor shall, within ten (10) days following acceptance of bid, notify the Architect/Owner of the sources of plant materials and bed preparation required for the project.
- Samples: Provide representative quantities of sandy loam soil, mulch, bed mix material, gravel, and crushed stone. Samples shall be approved by Architect before use on project.
- Product Data: Submit complete product data and specifications on all other specified materials.
- Submit three representative samples of each variety of omamental trees, shrubs, and groundcover plants for Architect's approval. When approved, tag, install, and maintain as representative samples for final installed plant materials.

Landscape Contractor to inspect all existing conditions and report any deficiencies to the Owner.

Maintenance of plant materials shall begin immediately after each plant is delivered to the site and shall continue until all construction has been satisfactorily accomplished.

Plant materials shall be delivered to the sile only after the beds are prepared and area ready for planting. All shipments of nursery materials shall be thoroughly protected from the dyingy maked during trainst. It plants which cannot be planted at once, after delivery to the site, shall be well protected against the possibility of dying by wind and sun. Balls of earth of 8.8 by plants shall be keypt covered with poll or other acceptable material. All

Notify the Landscape Architect for inspection and approval of all positioning of plant materials.

Excavate pits with vertical sides and horizontal bottom. Tree pits shall be large enough to permit handling and planting without injury to balls of earth or roots and shall be of such depth that, when planted and selfl

plants remain the property of the Contractor until final acceptance

Soil Analysis: Provide sandy loam soil analysis if requested by the Architect.

## JOB CONDITIONS

- General Contractor to complete the following punch list: Prior to Landscape Contractor initiating any portion of landscape installation, General Contractor shall leave planting bed areas three (5) inches bolow finish grade of oldewalks, drives and orube as shown on the drawings. All lawn areas to receive solid sod shall be left one (1") inch below the finish grade of sldewalks, drives, and oruts. All construction debris shall be removed prior to Landscape Contractor beginning any work.
- B. General Contractor shall provide topsoil as described in Section 02200 Earthwork.
- Storage of materials and equipment at the job site will be at the risk of the Landscape Contractor. The Owner cannot be held responsible for theft or damage.

### A. Maintenance

- The Landscape Contractor will be held responsible for the maintenance of all work from the time of planting until final acceptance by the Owner. No trees, shrubs, groundcover or grass will be accepted unless they show a healthy growth and
- satisfactory for glass with a cooperation of the satisfactory flag conditions.

  Maintenance shall include watering of trees and plants, cultivation, weeding spraying edging, pruning of trees, moving of grass, cleaning up and all other work necessary
- of maintenance. An written notice requesting final inspection and acceptance should be submitted to the Owner at least seven (7) days prior to completion. An on-site inspection by Owner and Leadscape Contractor will be completed prior to written acceptance. After final acceptance of installation, the Landscape Contractor will not be required to during of the stoppe liked work.

#### B. Guarantee:

- Trece shall be guaranteed for a twelve (12) month period after acceptance. Shrubs
  and groundcover shall be guaranteed for twelve (12) months. The Contractor shall
  replace all ideal materials as soon as weather permits and upon notification of the
  Owner. Plants, including trees, which have partially deta so that shape, size, or
  symmetry has been damaged, shall be concided or subject to replacement. In such
  cases, the opinion of the Owner shall be final.
   Plants is seed for represented shall be confided or subject to a shape size and triod as those.
  - sets, the opinion of the Womer shall be final.

    2 Plants used for replacement shall be of the same size and kind as those originally planted and shall be planted as originally specified. All work including materials, labor and equipment used in replacements, shall carry a twelve (12) month guarantee. Any damage, including rutis in lawn or bed areas, incurred as a result of making replacements shall be immediately
- repaired.

  At the direction of the Owner, plants may be replaced at the start of the next year's planting season. In such cases, dead plants shall be removed from the permises immediately.

  c. When plant replacements are made, plants, soil mix, fertilizer and mulch are to be utilized as originally specified and reinspected for full compliance with Contract requirements. All replacements are to be included under "Work" of this section.

- The Owner agrees that for the guarantee to be effective, he will water plants at least twice a week during dry periods and cultivate beds once a month after final
- acceptance.

  The above guarantee shall not apply where plants die after acceptance because of injury from storms, hail, freeze, insects, diseases, injury by humans, machines or theft.
- thetf. Acceptance for all landscape work shall be given after final inspection by the Owner provided the job is in a completed, undamaged condition, and there is a stand of grass in all lawn areas. At this time, the Owner will assume maintenance on the accepted work.
- Repairs: Any necessary repairs under the Guarantee must be made within ten (10) days after receiving notice, weather permitting, and in the event the Landscape Contractor does not make repairs accordingly, the Owner, without further notice to Contractor, may provide materials and men to make such repairs at the expense of the Landscape

### QUALITY ASSURANCE

- General: Comply with applicable Federal, State, County and Local regulations governing landscape materials and work
- Personnel: Employ only experienced personnel who are familiar with the required work Provide full time supervision by a qualified foreman acceptable to Landscape Architect.
- Selection of Plant Material:
  - . Make contact with suppliers immediately upon obtaining notice of contract acceptance to select and book materials. Develop a program of maintenance (pruning and fertilization) which will insure the purchased materials will meet and/or exceed project
  - territization yearnes are expedited to the expedite to the expedite exp
  - schedules to site.

    3. Owner and/or Architect shall inspect all plant materials when reasonable at place of growth for compliance with requirements for genus, species, cultivar/variety, size and quality.

    4. Owner and/or Architect retains the right to further inspect all plant material upon
- Owner after a thorust character than the figure of the condition of robats, paint intering inputs, arrival at the site and during missing in our state and exception of balls, jurisd, branching fallor, involved, improve, and lastic not dividuol. Owner and/or Architect may reject unsatisfactory or defective material at any time during the property of the condition of the cond

## 1.8 PRODUCT DELIVERY, STORAGE AND HANDLING

- Balled and Burlapped (B&B) Plants: Dig and prepare shipment in a manner that will not damage roots, branches, shape, and future development.
   Container Grown Plants: Deliver plants in rigid container to hold ball shape and protect root mase.

- Deliver packaged materials in sealed containers showing weight, analysis and name of manufacturer. Protect materials from deterioration during delivery and while stored
- at site.

  2. Deliver only plant materials that can be planted in one day unless adequate storage

- Deliver only plant materials that can be planted in one day unless adequate storage and watering facilities are available on pols into the storage and watering facilities are available on the sandwater or other approved moisture retaining material if not planted within 24 hours of delivery.
   Protect plants during delivery to prevent damage to root balls or destication of leaves. Keep plants most at all films. Cover all materials during transport.
   Notify Architect of delivery schodule 72 hours in advance so plant material may be observed upon arrival at job site.
   Remove rejected plant material immediately from site.
   To avoid damage or stress, do not lift, move, adjust to plumb, or otherwise manipulate plants by trunk or stems.

## PART 2 - PRODUCTS

### 2.1 PLANTS

- General: Well-formed No. 1 grade or better nursery grown stock. Listed plant heights are from tops of root balls to nominal tops of plants. Plant spread refers to nominal outer width of the plant, not to the outer losd fips. Plants will be individually approved by the Architect and his decision as to their acceptability shall be final.
- Quantities: The drawings and specifications are complimentary. Anything called for on one and not the other is as binding as if shown and called for on both. The plant schedule is an aid to bidders only. Confirm all quantities on plan.
- objectionable disfigurements, insect eggs and larvae and are to be of specimen quality
- Approval: All plant materials shall be subject to the approval of the Owner. All plants which are found unsuitable in growth, or in any unhealthy, badly shaped, or undersized condition, will be rejected by the Landscape Architect, either before or flet planting, and shall be removed at the oxponee of the Landscape Contractor and replaced with acceptable plants as specified.
- Trees shall be healthy, full branched, well shaped and shall meet the trunk diameter and height requirements of the plant schedule. Balls shall be firm, neat, slightly tapered, and well wrapped in burdip. Any tiee toose in the ball or with broken ball at time of planting will be rejected. Balls shall be ten (10) inched in diameter for each one (1) inch of trunk claimater. Measured six (or) inched above hall. Nomenclature conforms to the customary nursery usage: for clarification, the term Nomenclature conforms to the customary nursery usage: for clarification, the term "multi-trunk" defines a plant having three (3) or more trunks of nearly equal diameter

A = ROW SPACING B = ON CENTER SPACING

SPACE PLANTS IN A TRIANGULAR

12° MN EDGE OF BED

PLANT ROW SPACING 'D' ROW SPACING 'A' PLANTS/10SF

PREPARED SOIL MIX
PER SPECIFICATIONS

NOTE: NO STEEL EDGING TO BE INSTALLED ALONG SIDEWALKS

GROUNDCOVER PLANTING DETAIL

NOT TO SCALE

#### 2.2 SOIL PREPARATION MATERIALS

- Finable, fertile, dark, loamy soil, free of clay lumps, subsoil, stones and other extraneous material and reasonably free of weeds and foreign grasses. Loam containing Dallagrases or Nutgrase shall be rejected. Physical properties as follows:
  Clay Delween 7-27 percent
  Sit between 15-25 percent
  Sand less than 52 percent

- Sand less than 52 percent
  Organic matter shall be 3%-10% of total dry weight.
  If requested, provide a certified soil analysis conducted by an approved soil testing laboratory verifying that sandy loam meets the above requirements.
- Organic Material: Compost with a mixture of 80% vegetative matter and 20% animal waste. Ingredients should be a mix of course and fine textured material.
- Premixed Bedding Soil as supplied by Vital Earth Resources, Gladewater, Tex Professional Bedding Soil as supplied by Living Earth Technology, Dallas, Texas or Acid Gro Municipal Mix as supplied by Soil Building Systems, Dallas, Texas or approved equa
- Sharp Sand: Sharp sand must be free of seeds, soil particles and weeds.
- Mulch: Double Shredded Hardwood Mulch, partially decomposed, dark brown. Living Earth Technologies or approved equal.
- Commercial Fertilizer: 10-20-10 or similar analysis. Nitrogen source to be a minimum 50% slow release organic Nitrogen (3CU or UF) with a minimum 0% sulphur and 4% iron plue micronutrients.
- Peat: Commercial sphagnum peat moss or partially decomposed shredded pine bark or other approved organic material.

## MISCELLANEOUS MATERIALS

- Steel Edging: Shall be Ryerson "Estate Curbing", 1/8" x 4" with stakes 4" on center.

- . Post. Studded T-Post, #1 Armco with anchor plate, 6-0" length, paint green.
  2. Wire: 12 gauge, single strand, galvanized wire.
  3. Rubber hose: 2 ply, fiber reinforced hose, minimum ½ inch inside diameter. Color. Black.
- Filter Fabrio: Mirafi 140N by Celanese Fibers Marketing Company, available at Loftland Co., (214) 631-5250 or approved equal.

C. Gravel: Washed native pea gravel, graded 1 in. to 1-1/2 in.

**BROTHERS** STRICKLAND

HILLS,

UFE SNOW DR TH RICHLAND !

NORTH

ᆼ

CITY

LANDSCAPE ARCHITECT STUDIO GREEN SPOT, INC 1784 W. McDERMOTT DR.


SUITE 110


ALLEN, TEXAS 75013

CHRIS@STUDIOGREENSPOT.COM

469) 369-4448

# REFER TO PLANS FOR PLANT TYPES PREPARED SOIL MIX PER SPECIFICATIONS 1/2" MINIMUM BETWEEN TOP OF MULCH AND TOP OF CONCRETE — SIDEWALK Lawrence de agree





03 SIDEWALK / MULCH DETAIL

no steel along sidewalks

NOT TO SCALE

# Shrub and tree pits shall be no less than two (2) feet, twenty-four (24) inches, wider the the lateral dimension of earth ball and six (6) inches deeper than it's vertical dimension. Bemove and heul from site all rocks and stones over one (1) inch in diameter. Plants Dig a wide, rough sided hole exactly the same depth as the height of the ball, especially at the surface of the ground. The sides of the hole should be rough and jagged, never slick or glazed. Percolation Test: Fill the hole with water. If the water level does not percolate within 24 hours, the tree needs to move to another location or have drainage added. Install a PVC stand pipe per tree planting detail as approved by the Landscape Architect. Backfill only with 5 parts existing soil or sandy loam and 1 part bed preparation. When the hole is dug in soild rock, to pool from the same area should not be used. Carefully settle by watering to pervent air poolests. Remove the busing from the top 17.0 of the bell as well as all riylon, plastice siring and wire mesh. Container frees will usually be pot bound, if an offlow schander durses practice of two scending.

- 1. Propore new planting bode by scraping away existing grass and woods as necessary. Till existing soil to a depth of six (6") inches prior to placing compost and felializer. Apply fertilizer as per manufactures recommendations. Add six (6") inches of compost and till inches of six (6") inches of the topool. Apply organic fertilizer suich as Suistane or Green Sense at the rate of them (7.00) pounds per one thousand. (1,000) square feet.

  All planting areas shall receive a two (2") inch layer of specified mulch.

  Backfill for tree pits shall be as follows: Use existing top soil on site (use imported topsoil as needed) free from large dumps, rocks, delice, salicite, subsoils, etc., piaced in inte (9") inch layers and valence in thoroughly.
- 1. Areas to be Solid Sod Bermudagrass: Blocks of sod should be laid joint to joint, (staggered joints) after fertilizing the ground first. Roll grass areas to achieve a emooth, even surface. The jointe between the blocks of sod should be filled with lopsel where they are evidently gaped open, then watered thoroughly.
  2. Areas to be itydromulch Common Bermudagrass: itydromulch with bermudagrass seed at a rate of two (2) pounds per one thousand (1,000) equare feet. Use a 4 x 8' statler board against the bed areas. K Do not over prune Mulch the top of the ball. Do not plant grass all the way to the trunk of the tree. Leave the area above the top of the ball and mulch with at least two (2") inches of specified mulch.
  - All plant beds and trees to be mulched with a minimum settled thickness of two (2") inches over the entire bed or pit.

J. Do not wrap trees

- Obstruction below ground: In the event that rock, or underground construction work or obstruction are one-ordered in any plant pile seasonation work to be done under this section, alternate locations may be selected by the Owner. Where locations cannot be changed, the obstructions shall be removed to a depth of not less than three (37) feet below grade and not less than ones! of inner below the total total to high plant is properly set at the required grade. The work of this section shall include the removal for the stee of such rock or underground obstructions encounteed at the cost of the section shall enclude the removal free the stee of such rock or underground obstructions encounteed at the cost of the section shall enclude the removal free steep of the section shall enclude the removal free steep of such certain and the section shall enclude the removal free steep of such certain sections.
- Trees and large shrubs shall be staked as site conditions require. Position stakes to secure tree against seasonal prevailing winds.
- Dead wood or suckers and broken badly bruised branches shall be re tipping of the branched is not permitted. Do not cut terminal branche
- topping of the branched is not permitted. Lo not cut terminal trainches:

  2. Pruning shall be done with clean, sharp too holested, all tree pits shall be covered with a layer of organic material two (2") inches in depth. This limit of the organic material for trees shall be the diameter of the plant pit.


3.3 CLEANUP AND ACCEPTANCE


- Curbing shall be aligned as indicated on plans. Stake out limits of steel curbing and obtain Owners approval prior to installation.
- 2. All steel curtining shall be free of kinks and abrupt bends.
  3. Top of curbing shall be 3/4" maximum height above grade.
  1. Stakes are to be installed on the planting bed side of the curbing, as opposed to the

## grass side. Do not install steel edging along sidewalks. Cut steel edging at 45 degree angle where edging meets sidewalk

Cleanup: During the work, the premises shall be kept neat and orderly at all times. Storage areas for all meterials shall be so organized that they, too, are neat and orderly. All trash and debris shall be removed from the site as work progresses. Keep paved areas clean by sweeping or hosing at end of each days work.

END OF SECTION





(01) TREE PLANTING DETAIL

ISSUE:

DATE:

08.09.2022

SHEET NAME: LANDSCAPE DETAILS

SHEET NUMBER: