

TEXAS LOCAL GOVERNMENT PURCHASING COOPERATIVE BUYBOARD

Vendor: <i>RUSH TRUCK CENTER</i>	Date Prepared: <i>10/29/2018</i>
Contact for Vendor: <i>COLTON KRUSE</i>	Phone: <i>(830) 302-5219</i>
End User: <i>City of North Richland Hills</i>	
End User Contact: <i>Zane Ryan</i>	Phone/Fax: <i>(817) 427-6384</i>
Product Description: <i>Peterbilt 348 Dump Truck</i>	

A: Base Price in Bid/Proposal Number: 521-16			Series: 348 \$ 73,656.00		
B: Published Options(<i>Itemize Below</i>)					
	DESCRIPTION	AMOUNT	OPT #	DESCRIPTION	AMOUNT
Peterbilt	Meritor mT40-14X Axles/40K Peterbilt Air Trac	\$ 9,595.00	RTC-0051	21 Pt. Rush Care Package	\$ 1,236.00
Peterbilt	Allison 3500 RDS-P Transmission	\$ 10,603.00	RTC-0001	Dump Body	\$ 21,563.00
			RTC-1059	Lot Insurance	\$ 1,138.83
			RTC-1060	Floorplan Interest	\$ 1,142.63
Subtotal Column 1: \$ 20,198.00			Subtotal Column 2: \$ 25,080.46		
Published Options added to Base Price(<i>Subtotal of "Col 1" & "Col 2"</i>)					\$ 45,278.46

C: Subtotal of A + B					\$ 118,934.46
D: Non Published Options					
Subtotal Column 1:			Subtotal Column 2: \$ -		

Unpublished Options added to Base price (<i>Subtotal "Col 1 + Col 2"</i>)	
---	--

E: Contract Price Adjustment (<i>If any, explain here</i>)	
Price Level Increase	\$ 1,077.34

F: Total of C + D +/- E	\$ 120,011.80
-------------------------	---------------

G: Quantity ordered Units: <u>1.00</u> x F	\$ 120,011.80
--	---------------

H: BUYBOARD Administrative Fee	%	\$ 400.00
--------------------------------	---	-----------

I: Non-Equipment Charges & Credits (<i>I.e.: Ext. Warranty, Trade-In, Delivery, etc.</i>)					

J: TOTAL PURCHASE PRICE INCLUDING (G+H+I)	\$ 120,411.80
---	---------------



RTC Dallas MD D551
4200 Irving Blvd

City of N Richland Hills
4301 City Point

Dallas, Texas United States 75247
Phone: (214) 624-9103
Fax:
Email:

N Richland Hills, Texas United States 76180
Phone: (817) 427-6384
Fax:
Contact Email: zryan@nrhtx.com
Prepared for: Zane Ryan

Vehicle Summary

	Unit		Chassis	
Model:	Model 348	Fr Axle Load (lbs):		14600
Type:	Full Truck	Rr Axle Load (lbs)		40000
Description:	Pete 348 Dump Truck	G.C.W. (lbs):		66000
	Application	Road Conditions:		
Intended Serv.:	Construction Dump-On/Off Highway	Class A (Highway)		100
Commodity:	Concrete	Class B (Hwy/Mtn)		0
	Body	Class C (Off-Hwy)		0
Type:	End Dump	Class D (Off-Road)		0
Length (ft):	24	Maximum Grade:		6
Height (ft):	8.5	Wheelbase (in):		170
Max Laden Weight (lbs):	1000	Overhang (in):		54.8
	Trailer	Fr Axle to BOC (in):		69.8
No. of Trailer Axles:	0	Cab to Axle (in):		100.2
Type:		Cab to EOF (in):		155.0
Length (ft):	0	Overall Comb. Length (in):		263
Height (ft):	0.0			
Kingpin Inset (in):	0	Special Req.		
Corner Radius (in):	0	United States Registry		
	Restrictions			
Length (ft):	65			
Width (in):	102			
Height (ft):	13.5			

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

PACCAR FINANCIAL	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



RTC Dallas MD D551
4200 Irving Blvd

City of N Richland Hills
4301 City Point

Dallas, Texas United States 75247
Phone: (214) 624-9103
Fax:
Email:

N Richland Hills, Texas United States 76180
Phone: (817) 427-6384
Fax:
Contact Email: zryan@nrhtx.com
Prepared for: Zane Ryan

Data	Code	Description	\$ List	Weight
Base Model				
0003481	O	Model 348 The Model 348 was designed to exceed the rigid demands of Class 7 and Class 8 specialty application markets that require rugged durability and a wide range of optional content. The Model 348 represents a multi-dimensional performer with a GVW from 33,000 to 66,000 lbs. and optional capacity ratings to suit almost any vocation. The 348 is also available in a specifically designed all-wheel-drive configuration. From construction and crane service to utility and delivery services in both Class 7 and Class 8 markets, the 348 is in a class by itself.	106,946	10,610
0091290	O	Concrete	0	0
0093060	O	Construction Dump-On/Off Highway Truck or tractor without liftable trailing axle which carries bulk materials (excavated earth, sand/gravel, asphalt, demolition debris, etc.) and unloads by dumping out the back, over the side of the body, or out the bottom of the trailer.	0	0
0095170	O	End Dump	0	0
0098170	O	United States Registry	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514000	O	10-3/4in Steel Rails To 354in 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	609	228
0612230	O	Custom Wheelbase or Overhang Engineering approval may be required.	365	0
0613090	S	Three-Piece Crossmembers	0	58
0644090	S	EOF Square without Xmbr For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0

Front Axle & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
1012300	O	Meritor MFS14 14,600 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 14,600 pounds. Axle includes special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service. Combination of Meritor Easy Steer king pin bushings, computer-designed and optimized I-beam construction and stiff axle assembly delivering a tight turning radius, superior vehicle control and longer tire life.	502	62
1112150	O	Taper Leaf Springs, Shocks 14,600 lb	289	57
1233050	O	Power Steering TRW TAS85 For use with 14,600 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	512	7
1250180	S	Power Steering Reservoir Frame Mounted	0	0
1353545	O	PHP10 Aluminum PreSet Hubs	34	0
1380260	S	Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0	0
1380470	O	Meritor Wide Track IPO Standard, Front Axle MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles For improved turning radius.	0	15
1391410	O	Gusseted Cam Brackets, Steer Axle	24	0
1392970	O	Heavy Duty Cam Bushings, Steer Axle	26	0

Rear Axle & Equipment

1526150	O	Meritor MT40-14X 40,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	7,360	2,103
1616360	O	PHP10 Aluminum PreSet Hubs	92	-60
1631310	O	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	-8	0
1680450	O	Rear Brake Camshaft Reinforcement	94	9
1680460	O	Heavy Wall, Drive Axle(s)	520	88
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	24	2

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680950	S	Stability System Not Selected or Not Available	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1687348	O	Tandem Drive Axle (Model 348)	0	0
1705290	O	Ratio 5.29 Rear Axle	0	0
1821800	O	Peterbilt Air Trac 40,000 lbs, 52in Axle Spacing Light Weight	2,309	495
1920385	O	Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	52	0
1922260	O	Dash Mtd Dump Switch With Indicator Light For suspension	34	2

Engine & Equipment

2074306	O	PACCAR PX-9 300@2000 GOV@2200 860@1300 Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 75...Standard Maximum Speed Limit [LSL] N21330 N207 0...Expiration Distance N21350 P001 75...Maximum Accelerator Pedal Vehicle Speed N21370 P059 75...Maximum Cruise Speed N21400 N203 252..Reserve Speed Function Reset Distance N21410 N202 0...Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0...Reserve Speed Limit Offset N21440 P015 YES..Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 YES..Cruise Control Auto Resume	1,693	0
---------	---	---	-------	---

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
		N21480 P068 NO...Auto Engine Brake in Cruise		
		N21500 N209 0...Expiration Distance		
		N21510 P520 YES..Enable Idle Shutdown Park Brake Set		
		N21520 P030 5...Timer Setting		
		N21530 P233 YES..Enable Impending Shutdown Warning		
		N21540 P234 60...Timer For Impending Shutdown Warning		
		N21550 P516 35...Engine Load Threshold		
		N21570 P031 NO...Idle Shutdown Manual Override		
		N21590 P230 YES..Enable Hot Ambient Automatic Override		
		N21610 P172 40...Low Ambient Temperature Threshold		
		N21620 P173 60...Intermediate Ambient Temperature Threshold		
		N21630 P171 80...High Ambient Temperature Threshold		
2091310	O	Engine Idle Shutdown Timer Disabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372	O	Eff EIST NA Expiration Miles	0	0
2091640	O	Effective VSL Setting NA	0	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed	0	0
2521090	O	Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	82	2
2522050	U	PACCAR STARTER 12V	0	0
2522110	S	PACCAR 12V Starter N/A PACCAR MX Engines	0	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops	373	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	O	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	316	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	O	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	4	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0	0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	O	Exhaust Single RH Side Of Cab DPF/SCR RH Under Cab (2017).	392	29
3381770	O	Curved Tip Standpipe(s)	42	0
3387870	O	24in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	496	0

Transmission & Equipment

4052230	O	Allison 3500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-4.59, 2nd-2.25, 3rd-1.54, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.00)	10,603	195
4210080	S	1710 HD Driveline, 1 Midship Bearing	0	0
4250420	U	ALLISON 5TH GEN RDS, PKG 223	0	0
4252890	O	Allison FuelSense 2.0 Not Desired	0	0
4252950	O	Omit Allison Neutral At Stop	0	0
4256680	O	Allison 6-Speed Configuration, Wide Ratio Gears	0	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison Transmissions.	628	0

Air & Trailer Equipment

4510330	O	Bendix AD-IS EP Air Dryer with Heater And Coalescing Filter; Extended Purge	222	6
4520420	O	Pull Cords All Air Tanks	6	0
4540420	S	Nylon Chassis Hose	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4611930	O	Body Connections 5ft BOC Junction Box contains light and power circuits for Body Connections located 5ft from BOC.	135	4
4612780	O	A&E Conn EOF, 7-Way Socket & 4ft Additional Lines (coiled and strapped to frame, without gladhands)	240	0

Tires & Wheels

5069880	O	FF: BR 20ply 315/80R22.5 R249	752	66
5169430	O	RR: BR 14ply 11R22.5 M710 Ecopia Diameter = 41.8 inches; SLR = 19.5 inches	556	48
5190008	O	Code-rear Tire Qty 08	0	0
5210550	O	FF: Accur Stl Armor 29039PK 22.5X9.00 PHP10-5 Hand Holes	302	74
5310600	O	RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	340	136
5390008	O	Code-rear Rim Qty 08	0	0

Fuel Tanks

5554040	O	26in Aluminum 50 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	88	7
5602050	O	Location LH U/C 50 Gallon	0	0
5652900	O	DEF Tank Mounted LH Under Cab	80	0
5652990	O	Standard DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	S	DEF Tank Small	0	0

Battery Box & Bumper

6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	211	-84
6040550	S	Aftertreatment RH U/C ALUMINUM Non-Slip Cab Entry Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.	0	0
6121180	S	Steel Styled Aero Bumper Painted Cab Color 2 Tow pins	0	0

Cab & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0	0
6540120	O	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	134	39
6800360	O	Rubber Fender Lips 2 Inch Wide	97	8
6911700	S	Peterbilt UltraRide Driver Seat	0	0
6921700	S	Peterbilt UltraRide Passenger Seat	0	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939500	O	Air Ride Passenger	199	43
6939520	S	High Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7000015	S	Adjustable Steering Column - Tilt Only	0	0
7001620	S	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036120	S	Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0	0
7210430	O	Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	67	18
7210540	S	Day Cab Rear Window	0	0
7230060	S	One Piece Curved Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7330700	O	Peterbilt Comfort Control - Cab	21	6
7511010	O	Stainless Steel Mirrors 7x16 with Heat Element Right Click on Option to see Picture in Product Portfolio.	72	2
7560850	O	(2) Convex 8 Inch SS Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	240	4

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
7564110	O	Power Package Includes power door locks and power windows.	343	0
7610020	O	(1) Air Horn 15in Painted Mounted under cab.	172	8
7725710	O	Standard Speaker Package For Cab (2) Speakers	118	4
7725715	O	ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	324	10
7788140	O	Radio Antenna Mounted on LH Mirror Bracket	34	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7851780	O	CabMate Cab Air Suspension Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	766	15
7900090	O	Triangle Reflector Kit Shipped Loose	17	13
7900270	O	Fire Extinguisher; Cab Mounted Hazmat approved UL listed/rated ABC.	54	8
7901130	O	Backup Alarm (107dB)	53	3
8011400	O	Main Transmission Oil Temperature Gauge Located in Driver Information Display	13	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall.	0	0
8032420	O	Buzzer On Air Suspension Dump Valve Requires dash mounted dump valve (1922260)	10	0
8071340	O	Bright Bezel Gauges	50	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED Light Emitting Diodes	0	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup LH/RH Square EOF or Dropped A-Brace	0	0

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
Paint				
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - 809956EY INGOT SILVER N85400 HOOD TOP 809956EY INGOT SILVER N85500 CAB ROOF 809956EY INGOT SILVER N85200 FRAME L0001EA BLACK N85700 BUMPER 809956EY INGOT SILVER N85300 FENDER 809956EY INGOT SILVER	0	0
8531320	O	Axalta Two Stage Effect - Metallic/Pearl Cab/Hood & Sleeper Only	443	0
Options Not Subject To Discount				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9408931	O	PDI At Excellence Peterbilt Location	230	0
Miscellaneous				
9409800	O	2017 EPA Emissions Engine Warranty Only	0	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)	\$140,572
Freight Charge	\$2,400
Options Not Subject to Discount	\$230
Surcharges Not subject to Discount	\$0
Total Weight	14340

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:47:12 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
7564110	O	Power Package Includes power door locks and power windows.	343	0
7610020	O	(1) Air Horn 15in Painted Mounted under cab.	172	8
7725710	O	Standard Speaker Package For Cab (2) Speakers	118	4
7725715	O	ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	324	10
7788140	O	Radio Antenna Mounted on LH Mirror Bracket	34	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7851780	O	CabMate Cab Air Suspension Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	766	15
7900090	O	Triangle Reflector Kit Shipped Loose	17	13
7900270	O	Fire Extinguisher; Cab Mounted Hazmat approved UL listed/rated ABC.	54	8
7901130	O	Backup Alarm (107dB)	53	3
8011400	O	Main Transmission Oil Temperature Gauge Located in Driver Information Display	13	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall.	0	0
8032420	O	Buzzer On Air Suspension Dump Valve Requires dash mounted dump valve (1922260)	10	0
8071340	O	Bright Bezel Gauges	50	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED Light Emitting Diodes	0	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup LH/RH Square EOF or Dropped A-Brace	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:48:40 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Data	Code	Description	\$ List	Weight
Paint				
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - 809956EY INGOT SILVER N85400 HOOD TOP 809956EY INGOT SILVER N85500 CAB ROOF 809956EY INGOT SILVER N85200 FRAME L0001EA BLACK N85700 BUMPER 809956EY INGOT SILVER N85300 FENDER 809956EY INGOT SILVER	0	0
8531320	O	Axalta Two Stage Effect - Metallic/Pearl Cab/Hood & Sleeper Only	443	0
Options Not Subject To Discount				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9408931	O	PDI At Excellence Peterbilt Location	230	0
Miscellaneous				
9409800	O	2017 EPA Emissions Engine Warranty Only	0	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)	\$140,572
Freight Charge	\$2,400
Options Not Subject to Discount	\$230
Surcharges Not subject to Discount	\$0
Total Weight	14340

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 8:48:40 AM	Complete	Model Number:	Model 348
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q24655188
Prepared by:	Administrator		Version Number:	38.02



Quote WTTLLC00009078 Page 1 of 3 Date 10/26/2018

Warren Truck and Trailer, LLC
 15768 US HIGHWAY 271 NORTH
 Talco TX 75487

Phone (888) 734-4400
 Fax (903) 379-4400
 WarrenTruckAndTrailer.com

Bill To	Ship To	Contact
RUSH ENTERPRISES/RUSH TRUCK CENTER RUSH MEDIUM DUTY TRUCKS 4200 IRVING BLVD DALLAS TX 75247	RUSH ENTERPRISES/RUSH TRUCK CENTER RUSH MEDIUM DUTY TRUCKS 4200 IRVING BLVD DALLAS TX 75247	DANIEL (972) 655-9463 Ext. 0000

Purchase Order No.	Customer ID	Salesperson ID	Shipping Method	Payment Terms	Req Ship Date	Master No.
	RUS401	MACK	DELIVERED	Net30	0/0/0000	10,015,262
QTY	Item Number	Description	UOM	Unit Price	Ext. Price	
1	FL-13	DUMP BODY - FRAMLESS - 13' CITY OF NORTH RICHLAND HILLS Yardage 11/13 Floor / Material 1/4" A-1011 Front / Material 48" 7 GA A1011 Side / Material 42" 7 GA A1011 4" STRUCTURAL CROSS-MEMBERS ON 10" C/L Vertical Side Brace Yes Horizontal Brace No Hoist / Cylinder VTLW-63110 Hydraulics Yes	EA	\$21,710.00	\$21,710.00	
1	TAILGATE	Air Operated Yes Panel 9 Material 1/4" A-1011 Height 48 Slope None Chains 5/16" Double Acting Yes LIFTING HOOKS INSTALLED ON TOP EDGE FOR REMOVAL OF GATE	Each	\$0.00	\$0.00	
1	DB OPTIONS # 1	Cabshield Full Width 1/2 Asphalt Apron 9" (BOLT ON) Bolt On Yes Body Lights LED Oval S/T/T (2) PER EACH REAR POST*** STEPS ON BODY D/S FRONT w/ (2) STEPS BELOW RUBRAIL & (2) STEPS INSIDE BODY	Each	\$0.00	\$0.00	
1	DB INSTALL	Hydraulic Oil 30 Gal Hydraulic Hoses/Fittings Yes Pump 22 gal CW (CONTINUOUS-DUTY) Console Clutch Shift / Air Misc Mounting Material Conspicuity Tape No Mudflaps and Brackets Yes Chrome Turnouts No Splash/Gravel Guards Yes Side Boards Channel -2x6 (FLAT SIDE OUT - WELDED) Covers No Delivery Fuel/Charges Yes	Each	\$0.00	\$0.00	
1	PAINT	Warren Black (800-80007)	Each	\$0.00	\$0.00	



Quote WTTLLC00009078 Page 2 of 3 Date 10/26/2018

Warren Truck and Trailer, LLC
 15768 US HIGHWAY 271 NORTH
 Talco TX 75487

Phone (888) 734-4400
 Fax (903) 379-4400
 WarrenTruckAndTrailer.com

Purchase Order No.	Customer ID	Salesperson ID	Shipping Method	Payment Terms	Req Ship Date	Master No.
	RUS401	MACK	DELIVERED	Net30	0/0/0000	10,015,262
QTY	Item Number	Description	UOM	Unit Price	Ext. Price	
1	PTO	POWER TAKE OFF Muncie CS Series (Auto)	EA	\$0.00	\$0.00	
1	TARP SYSTEM	TARP system Installed DONOVAN MOD. #5000 XGL SIDE-FLAT TORSION SPRING MANUAL GROUND LEVEL CRANK SYS. WIND DEFLECTOR BLACK MESH TARP	EA	\$0.00	\$0.00	
1	TOW PACKAGE	Pintle Plate 3/4" Pintle Hitch 15 Ton (BP-100-A) SWIVEL, SPRING CUSHIONED Glad Hands No (AIR-LINES CAPPED AT END OF FRAME) D Rings Yes Tow Hooks No Electric Plug 7-WAY RV TYPE (TOP EDGE OF PLATE) Pup Rigging No (2) 4" ROUND LED S/T/T GROMMET MOUNTED IN PLATE (2) LED REVERSE RUBBER GROMMET MOUNTED IN BRACKETS (1 EACH SIDE OF PLATE) SINGLE EYELET NEAR TOP OF PINTLE PLATE FOR TRAILER "BREAK-AWAY CABLE) ELECTRIC BRAKE CONTOLLER-INSTALLED	Each	\$0.00	\$0.00	
1	SPECIAL HYDRAULICS	POWER BEYOND AND SPREADER CONTROLS FURNISHED & INSTALLED TO OPERATE MONROE MSV-144-84-50 V-BOX SAND SPREADER. HYDRAULIC HOSES EXTENDED TO PINTLE PLATE TO OPERATE SPREADER w/ QUICK DISCONNECT FITTINGS (SS) TO INCLUDE DUST CAPS. SIDE MOUNT HYDRAULIC TANK w/ 10 MICRON RETURN LINE FILTER	Each	\$0.00	\$0.00	
1	DELIVERED - DALLAS	DELIVERY TO RUSH PETERBILT - IRVING BLVD. - DALLAS DELIVERY CHARGES SHOWN IN SHIPPING COLUMN BELOW	Each	\$0.00	\$0.00	



Quote WTTLLC00009078 Page 3 of 3
Date 10/26/2018

Warren Truck and Trailer, LLC
15768 US HIGHWAY 271 NORTH
Talco TX 75487

Phone (888) 734-4400
Fax (903) 379-4400
WarrenTruckAndTrailer.com

Quotation reviewed and accepted by:
(signed) _____
Please fax back to us for entry as an order
NOTE: Quotation good for 10 days only

Subtotal	\$21,710.00
Misc	\$0.00
Tax	\$0.00
Ship & Handling	\$350.00
Trade In Allowance	\$0.00
Total	\$22,060.00