TEXAS LOCAL GOVERNMENT PURCHASING COOPERATIVE BUYBOARD

Vendor RUSH TRUCK CE	ENTER	Date Prepared	10/24/2018
Contact for Vendor: COLTON KRUSE	*	Phone (830) 302-5219	
End User: City of North Richla	and Hills		
End User Contact: Zane Ryan		Phone/Fax (817) 427-6384	
Product Description: Peterbilt 337 Chass.	is		
A: Base Price in Bid/Proposal Number:	521-16	Series: 337	\$ 67,500.00
B: Published Options(Itemize Below)			
DESCRIPTION	AMOUNT	OPT# DESCRIPTION	AMOUNT
Peterbilt Frame & Equipment	\$ 1,309.00	Peterbilt Fuel Tanks/Battery Box & Bumper	
Peterbilt Front Axle & Equipment	\$ 62.00	Peterbilt Cab & Equipment	\$ 3,047.00
Peterbilt Rear Axle & Equipment	\$ 1,723.00	Peterbilt Paint	\$ 442.00
Peterbilt Engine & Equipment	\$ 4,368.00	RTC-0053 Body Prep Package	\$ 2,438.00
Peterbilt Transmission & Equipment	\$ 10,723.00	RTC-0126 500E	\$ 121,641.00
Peterbilt Air & Trailer Equipment	\$ 507.00	RTC-1059 Lot Insurance	\$ 198.61
Peterbilt Tires & Wheels	\$ 1,131.00	RTC-1060 Dealership Floorplan Interest	\$ 197.83
Subtotal Column 1: \$ 19,823.00		Subtotal Column 2: \$ 128,077.44	
Published Options added to Base Price(Subtotal of "Col	1" & "Col 2")	\$ 147,900.44
C: Subtotal of A + B			\$ 215,400.44
D: Non Published Options			
Etnyre 2000 Gallon Blacktopper Per Contract #: 515-016	\$ (17,089.00)		
Subtotal Column 1: \$ (17,089.00)		Subtotal Column 2: \$ -]
III	(0.11.4.110.1		A (47,000,00)
Unpublished Options added to Base price	e (Subtotal "Col	1 + Coi 2")	\$ (17,089.00)
E: Contract Price Adjustment (If any, ex	nlain here \		
Price Level Increase	prain nord)		\$ 1,077.34
			7
F: Total of C + D +/- E			\$ 199,388.78
			<u></u>
G: Quantity ordered Units:	1.00	хF	\$ 199,388.78
H: BUYBOARD Administrative Fee		%	\$ 400.00
I: Non-Equipment Charges & Credits (I.	e.: Ext. Warranty	v, Trade-In, Delivery, etc.)	
	L		<u> </u>
J: TOTAL PURCHASE PRICE INCLUD	ING (G+H+I)		\$ 199,788.78
o. 101/121 OROH/OET MOEDINGEOD	(3.11.1)		Ψ 133,700.70

CUSTOMIZED PRODUCT PRICING SUMMARY BASED ON CONTRACT BUYBOARD 515-016

]	End User: City of North Richlar	nd Hills	R.B Ever	ett & Co. Rep:	Kirk Te	dford
	Contact: Zane Ryan		_	Date:	10/15/2	2018
	Product: Etnyre 2000 gallon Black	topper Dist.		A. Base Price:	101,00	0.00
D	Dublished Ontions (Itamiza anah Pal	om)	-			
Б.	Published Options (Itemize each Belo OPTIONS	PRICE		OPTIONS		PRICE
	Power Washdown	600.00		Cone strainer		160.00
	12 t spray bar	Std	Ţ	PTO of Transmission	n	700.00
	Diesel	15.00	1	x 4 Rubber Load h		470.00
	Suction Override	180.00	12	Safety Strobe	1030	550.00
	Wet Storage	300.00		Back-Up Alarm		180.00
	6- 1Ft. Extensions @520	3,120.00		Васк Ор гнагиг		100.00
	(18 feet total bar length)	3,120.00				
	(18 feet total bal length)					
		<u>!</u>	1	Total of B Publish	ned Ontions:	6,275.00
C	Unpublished Options (Itemize each b	elow not to	exceed 25%)	10101 01 2 1 501101	opuous.	0,270,00
О.	OPTION	PRICE	onocca 25 / 0)	OPTION		PRICE
	0111011					11402
		1	To	otal of C. Unpublish	ned Options:	0.00
	TOTAL LIST PRICE			·····		107,275.00
D.				Discount:	6%	6,436.50
Б. Е.	Freight Charges			Diocount.	0,0	4,000.00
F.	Total $A + B + C + D + E = F$					104,838.50
G.	Quanity Ordered	1	x F =			104,838.50
О. Н.	Non-Equipment Charges & Credits	1		P.D.I.	ļ	2,000.00
11,	Non-Equipment Charges & Credits	Δ Α.	ditional R	B Everett Govt	Discount:	2,000.00

TOTAL PURCHASE PRICE

104,552.00



RTC Dallas MD D551 4200 Irving Blvd City of N Richland Hills

4301 City Point

Dallas, Texas United States 75247

Phone: Fax:

Email:

(214) 624-9103

N Richland Hills, Texas United States 76180

Phone:

(817) 427-6384

Fax:

Contact Email: zryan@nrhtx.com

Prepared for: Zane Ryan

Vehicle Summary

	Unit	Chassis	
Model:	Model 337	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs)	21000
Description:	Entyre Liquid Asphalt Dist	G.C.W. (lbs):	33000
	Application	Road Conditions:	
Intended Serv.:	Utility/Lube Service	Class A (Highway)	100
Commodity:	Petroleum Products	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
_	Body	Class D (Off-Road)	0
Type:	Lube Service	Maximum Grade:	6
Length (ft):	18	Wheelbase (in):	190
Height (ft):	13.5	Overhang (in):	100
Max Laden Weight	(lbs): 1000	Fr Axle to BOC (in):	69.8
	T	Cab to Axle (in):	120.2
	Trailer	Cab to EOF (in):	220.2
No. of Trailer Axles:	0	Overall Comb. Length (in):	328
Type:			
Length (ft):	0	Special Req.	
Height (ft):	0.0	United States Registry	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
	Restrictions		
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		
Approved by:		Date:	

Note: All sales are F.O.B. designated plant of manufacture.

PACAR FINANCIAL Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: Effective Date: 10/23/2018 1:47:47 PM

Complete

Model Number: Quote/DTPO/CO:

Model 337 Q14655111

Prepared by:

Jul 1, 2018 Administrator

Version Number:

37.11

33623-8357-1598 Page 1 of 10



RTC Dallas MD D551 4200 Irving Blvd

City of N Richland Hills 4301 City Point

Dallas, Texas United States 75247 Phone: (214) 624-9103

Fax:

Email:

N Richland Hills, Texas United States 76180 Phone: (817) 427-6384

Fax:

Contact Email: zryan@nrhtx.com Prepared for: Zane Ryan

Data	Code	Description	\$ List	Weight
Base Mode	el .			
0003371	0	Model 337 The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	92,839	10,070
0091130	0	Petroleum Products	0	0
0093140	0	Utility/Lube Service Truck used to service construction and mining equipment. Includes bodies such as, mechanics service bodies, tire hoists, fuel/lube, boom, etc.	0	0
0095300	0	Lube Service	0	0
0098170	0	United States Registry	0	0
Configurat	ion			
0200699		Other Secondary Manufacturer (Specify by narrative) N02000 Tim King N02010 R B Everett & Co N02020 O(817)299-0010 N02030 C(817)454-5838	0	0
Frame & E	guipmen	t		
0515010		10-5/8in Steel Rails 326-384 in 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	249	259
0612090	0	190in Wheelbase	0	0
0612230	0	Custom Wheelbase or Overhang Engineering approval may be required.	365	0
0613090	0	Three-Piece Crossmembers	695	0
0644090	S	EOF Square without Xmbr For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
***************************************			AA-1400000000000000000000000000000000000	

Front Axle & Equipment

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.						
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337		
Effective Date:	Jul 1, 2018	•	Quote/DTPO/CO:	Q14655111		
Prepared by:	Administrator		Version Number:	37.11		

Page 2 of 10 33623-8357-1598



Data	Code	Description	\$ List	Weight
1012130	0	Meritor MFS+12 12,000 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service	0	33
1111190	0	Taper Leaf Springs, Shocks 12,000 lb	38	0
1243040	S	Power Steering Sheppard HD94 For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	0	Power Steering Reservoir Frame Mounted	0	0
1353545	S	PHP10 Aluminum PreSet Hubs	0	0
1380260	S	Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0	0
1380470	0	Meritor Wide Track IPO Standard, Front Axle MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles For improved turning radius.	0	5
1391410	0	Gusseted Cam Brackets, Steer Axle	24	0
1513400	0	Dana Spicer 21065T 21,000 lb Two Speed	937	193
1616370	0 S	PHP10 Iron PreSet Hubs Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	-33 0	0
1616370	0	PHP10 Iron PreSet Hubs Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car		
1616370 1631310	O S	PHP10 Iron PreSet Hubs Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	0	0
1616370 1631310 1680280	O S	PHP10 Iron PreSet Hubs Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. Bendix Smart ATC Traction Control	0 225	2
1616370 1631310 1680280 1680450	0 S 0 0	PHP10 Iron PreSet Hubs Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. Bendix Smart ATC Traction Control Rear Brake Camshaft Reinforcement	0 225 93	2 9
1616370 1631310 1680280 1680450 1680490 1680500	0 S 0 0	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. Bendix Smart ATC Traction Control Rear Brake Camshaft Reinforcement Gusseted Cam Brackets, Drive Axle(s) SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air	0 225 93 24	0 2 9 2
1616370 1631310 1680280 1680450 1680490 1680500	O S O O S S	PHP10 Iron PreSet Hubs Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. Bendix Smart ATC Traction Control Rear Brake Camshaft Reinforcement Gusseted Cam Brackets, Drive Axle(s) SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0 225 93 24 0	0 2 9 2 0
1616370 1631310 1680280 1680450 1680490 1680500	O S O O S S	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. Bendix Smart ATC Traction Control Rear Brake Camshaft Reinforcement Gusseted Cam Brackets, Drive Axle(s) SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. Stability System Not Selected or Not Available	0 225 93 24 0	0 2 9 2 0
1616370 1631310 1680280 1680450 1680490 1680500 1681337 1682430	O S O O S S S S	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. Bendix Smart ATC Traction Control Rear Brake Camshaft Reinforcement Gusseted Cam Brackets, Drive Axle(s) SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. Stability System Not Selected or Not Available Single Drive Axle (Model 337) Anti-Lock Braking System (ABS) 4S4M	0 225 93 24 0	0 2 9 2 0
1616370 1631310 1680280 1680450 1680490 1680500 1681337 1682430 1687020	O S O O S S S S S	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. Bendix Smart ATC Traction Control Rear Brake Camshaft Reinforcement Gusseted Cam Brackets, Drive Axle(s) SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. Stability System Not Selected or Not Available Single Drive Axle (Model 337) Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system. Bendix Air Cam Rear Drum Brakes 16.5x8.6 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0 225 93 24 0	0 2 9 2 0

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337	
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q14655111	

Prepared by:

Quote/DTPO/CO:

Q14655111

Administrator

Version Number:

37.11



Data	Code	Description	\$ List	Weight
1911280	0	Reyco Helper Springs 3,000 lbs For use with Reyco 79KB suspension	375	60
Engine & E	quipme	nt		
2074306	0	PACCAR PX-9 300@2000 GOV@2200 860@1300 Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 75Standard Maximum Speed Limit [LSL] N21330 N207 0Expiration Distance N21350 P001 64Maximum Accelerator Pedal Vehicle Speed N21360 P110 0Accelerator Lower Droop N21370 P059 64Maximum Cruise Speed N21380 P111 0Cruise Control Lower Droop N21400 N203 252Reserve Speed Function Reset Distance N21410 N202 0Maximum Cycle Distance N21420 N206 10Maximum Active Distance N21430 N201 0Reserve Speed Limit Offset N21440 P015 YESEngine Protection Shutdown N21450 P026 NOGear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NOGear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NOCruise Control Auto Resume N21480 P068 NOAuto Engine Brake in Cruise N21510 P520 YESEnable Idle Shutdown Park Brake Set N21520 P030 5Timer Setting N21530 P233 YESEnable Impending Shutdown Warning N21540 P234 60Timer For Impending Shutdown Warning N21540 P234 60Timer For Impending Shutdown Warning N21540 P234 60Timer For Impending Shutdown Warning N21540 P230 YESEnable International National Overrule N21590 P230 YESEnable Hot Ambient Automatic Overrule N21590 P230 YESEnable Hot Ambient Automatic Overrule N21630 P173 60Intermediate Ambient Temperature Threshold N21630 P171 80High Ambient Temperature Threshold	1,693	0
2091310	0	Engine Idle Shutdown Timer Disabled Eff EIST NA Expiration Miles	0	0
2091640	0	Effective VSL Setting NA	0	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2141990	0	Omit Chevron Engine Oil Sticker (DELO)	-4	0
2513060	S	PACCAR 160 Amp Alternator, Brushed	0	0
2522050	S	PACCAR 12V Starter	0	0

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337	
Effective Date:	Jul 1, 2018	•	Quote/DTPO/CO:	Q14655111	
Prepared by:	Administrator		Version Number:	37.11	

33623-8357-1598 Page 4 of 10



Data	Code	Description	\$ List	Weight
2535040	0	3 Optima DT31T Batteries 2700 CCA Threaded Stud type terminal. AGM (Absorbent Glass Material). Stranded copper battery cables are double aught (00) or larger to reduce resistance.	783	55
2539030	0	Battery Disconnect Switches (2) Mounted in Cab LH Side of Driver Seat	558	9
2539410	0	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	99	4
2539550	Ο	Batteries In In-Cab Battery Box	0	0
2621030	0	On/Off Fan Clutch	54	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	0	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	316	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	0	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	4	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.		0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	O	Exhaust Single RH Side Of Cab DPF/SCR RH Under Cab (2017).	300	29
3381770	0	Curved Tip Standpipe(s)	42	0
3387890	0	36in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	523	4

Transmission & Equipment

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337	
Effective Date:	Jul 1, 2018	-	Quote/DTPO/CO:	Q14655111	
Prepared by:	Administrator		Version Number:	37.11	

33623-8357-1598 Page 5 of 10



Codo		61. (
Code	Description	\$ List	Weight
0	Allison 3500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-4.59, 2nd-2.25, 3rd-1.54, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.00)	10,099	195
S	1710 HD Driveline, 1 Midship Bearing	0	0
0	Allison FuelSense 2.0 Not Desired	0	0
0	Omit Allison Neutral At Stop	0	0
0	Allison 6-Speed Configuration, Wide Ratio Gears	0	0
	Dash Mounted Push Button Shifter Available with Allison Transmissions.	624	0
	Bendix AD-IS Air Dryer W/Heater	0	0
0	Pull Cords All Air Tanks	6	0
S	Nylon Chassis Hose	0	0
S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
0	Clear Inside Frame of All Air System Components LH BOC	501	0
0	FF: BR 14Ply 11R22.5 R283A Ecopia RR: BR 14ply 11R22.5 M770	80 802	-4 60
	Diameter = 42.2 inches; SLR = 19.8 inches		
		_	0 34
	Heavy Duty, 2 Hand Holes RR: Accur Stl Armor 50291PK 22.5X8.25	166	68
0	Code-rear Rim Qty 04	0	0
	o O s o O er Equip s o O o O o O o O o O o O o O	Allison 3500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation). Forward Ratios: 1st-4.59, 2nd-2.25, 3rd-1.54, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.00). S 1710 HD Drivelline, 1 Midship Bearing. Allison FuelSense 2.0 Not Desired. O mit Allison Neutral At Stop. Allison 6-Speed Configuration, Wide Ratio Gears. Dash Mounted Push Button Shifter. Available with Allison Transmissions. Bendix AD-IS Air Dryer W/Heater. And Coalescing Filter. Pull Cords All Air Tanks. Nylon Chassis Hose. S Steel Painted Air Tanks. All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. C Clear Inside Frame of All Air System Components LH BOC RE: BR 14Ply 11R22.5 M770 Diameter = 42.2 inches; SLR = 19.8 inches. C Code-rear Tire Qty 04 FF: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Z Hand Holes RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	Allison 3500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-4.59, 2nd-2.25, 3rd-1.54, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.00) S 1710 HD Driveline, 1 Midship Bearing O Allison FuelSense 2.0 Not Desired O Omit Allison Neutral At Stop O Allison 6-Speed Configuration, Wide Ratio Gears O Dash Mounted Push Button Shifter Available with Allison Transmissions. er Equipment S Bendix AD-IS Air Dryer W/Heater And Coalescing Filter O Pull Cords All Air Tanks S Nylon Chassis Hose S Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the framer arils will be polished aluminum). Peterbilit will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. O Clear Inside Frame of All Air System Components LH BOC Neels O FF: BR 14Ply 11R22.5 R283A Ecopia O RR: BR 14ply 11R22.5 M770 Diameter = 42.2 inches; SLR = 19.8 inches O Code-rear Tire Qty 04 O FF: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, 2 Hand Holes O RP: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, 17 Wo Hand Holes

Fuel Tanks

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337	
Effective Date:	Jul 1, 2018	-	Quote/DTPO/CO:	Q14655111	
Prepared by:	Administrator		Version Number:	37.11	

33623-8357-1598 Page 6 of 10



Data	Code	Description	\$ List	Weight
5554040	0	26in Aluminum 50 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	-119
5602050	0	Location LH U/C 50 Gallon	0	0
5652900	0	DEF Tank Mounted LH Under Cab	77	0
5652990	0	Standard DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	0	DEF Tank Small	-108	0
Battery Bo	x & Bum	per		
6010390		Omit Standard Battery Box Use with passenger seat/in-cab battery box codes only	-247	-45
6030540	0	Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete	391	0
6040550	S	Aftertreatment RH U/C AlumINUM Non-Slip Cab Entry Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.	0	0
6121180	S	Steel Styled Aero Bumper Painted Cab Color 2 Tow pins	0	0
Cab & Equ i 6510110		Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0	0
6540120	0	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	131	39
6540160	0	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	19	2
6911700	S	Peterbilt UltraRide Driver Seat	0	0
6921700	0	Peterbilt UltraRide Passenger Seat	-163	0
6939070	0	Mounted On In-Cab Battery Box For use with non-air passenger seats only. Includes battery quick disconnect located under driver side door.	853	39
6939400	0	Air Ride Driver	195	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939520	0	High Back Passenger	28	0
6939570	S	Vinyl Passenger	0	0
7001520	0	Adjustable Steering Column - Tilt/Telescope	113	11

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337	
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q14655111	
Prepared by:	Administrator		Version Number:	37.11	

33623-8357-1598 Page 7 of 10



Data	Code	Description	\$ List	Weight
7001620	S	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036120	S	Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0	0
7210420	0	Dark Window Tint ipo STD Tint - Day Cab	21	0
7210430	0	Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	67	0
7210540	S	Day Cab Rear Window	0	0
7230060	S	One Piece Curved Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi- Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7330700	0	Peterbilt Comfort Control - Cab	21	6
7561180	0	Aero Mirrors Ea Side Htd & Mtrzd 4-Way Adjustable Bright Finish with Convex	521	4
7564110	0	Power Package Includes power door locks and power windows.	341	0
7610020	0	(1) Air Horn 15in Painted Mounted under cab.	172	8
7725710	0	Standard Speaker Package For Cab (2) Speakers	118	4
7725715	O	ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	324	10
7788140	0	Radio Antenna Mounted on LH Mirror Bracket	34	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7900090	0	Triangle Reflector Kit Shipped Loose	17	13
7900270	0	Fire Extinguisher; Cab Mounted Hazmat approved UL listed/rated ABC.	54	8
7901130	0	Backup Alarm (107dB)	53	3
8011400	0	Main Transmission Oil Temperature Gauge Located in Driver Information Display	13	0
8021380	S	Air Restriction Indicator Mounted on air cleaner,intake piping, or firewall.	0	0

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337	
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q14655111	
Prepared by:	Administrator		Version Number:	37.11	

33623-8357-1598 Page 8 of 10



Data	Code	Description	\$ List	Weight
8071340	0	Bright Bezel Gauges	0	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED Light Emitting Diodes	0	0
8133470	0	Switch & Wiring For F/O Beacon/Strobe 10 ft coiled wire BOC/BOS at rear sill	55	2
8133960	0	Daytime Running Lights Required on all Canadian vehicles	60	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup LH/RH Square EOF or Dropped A-Brace	0	0
Paint	C	(4) Colon Avelto Two Stones Colollilos d	0	0
8530770	5	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - 809956EY INGOT SILVER N85400 HOOD TOP 809956EY INGOT SILVER N85500 CAB ROOF 809956EY INGOT SILVER N85200 FRAME N0001EA BLACK N85700 BUMPER 809956EY INGOT SILVER N85300 FENDER 809956EY INGOT SILVER	0	0
8531320	O	Axalta Two Stage Effect - Metallic/Pearl Cab/Hood & Sleeper Only	442	0
Ontions No	nt Subjec	ct To Discount		
9400091		Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9408931	0	PDI At Excellence Peterbilt Location	230	0
Miscellane		2047 FDA Fusicaione Fusina	^	^
9409800	U	2017 EPA Emissions Engine Warranty Only	0	O

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	10/23/2018 1:47:47 PM	Complete	Model Number:	Model 337	
Effective Date:	Jul 1, 2018	•	Quote/DTPO/CO:	Q14655111	
Prepared by:	Administrator		Version Number:	37.11	

33623-8357-1598 Page 9 of 10



Data	Code	Description	\$ List	Weight
9409960	0	Presentation Created Using Featured Spec For Model	0	0
Freight Cha Options Not	irge t Subject	(W/O Freight & Warranty & Surcharges) to Discount		\$116,264 \$2,300 \$230
Surcharges Total Weigh	•	ject to Discount		\$0 11072

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:

10/23/2018 1:47:47 PM

Complete

Model Number:

Model 337

Effective Date:

Jul 1, 2018

Quote/DTPO/CO:

Q14655111

Prepared by:

Administrator

Version Number:

37.11

33623-8357-1598