ORDINANCE 3886 SUMMARY OF SIGN REGULATIONS REVISIONS JANUARY 2025

ELECTRONIC MESSAGE SIGNS

Section 106-2 - Definitions

- Delete existing definition for electronic message board
- Add definition for <u>electronic message</u> <u>sign</u>
- Revise definition for ground sign to change <u>electronic message board</u> to <u>electronic message sign</u>

Section 106-3 – General regulations

- (12) Freeway overlay zone
 - Revise subsections a through d to replace <u>electronic</u> <u>message board</u> with <u>electronic message sign</u>

Section 106-5 – Prohibited signs

(2) Rotating and flashing signs

 Delete second sentence: Flashing or blinking lights which are incorporated into an electronic message board may be allowed and are regulated elsewhere in the regulations of this chapter.

Section 106-9 – Table of permitted signs

- Revise section A. Ground Signs to change <u>electronic message board</u> to <u>electronic message sign</u> in table and footnote 4
- Revise footnote 4 to change <u>electronic message board</u> to electronic message sign

Section 106-12 – Electronic message boards and digital billboards

- Revise caption to read <u>Electronic</u> message signs and digital billboards
- Delete subsection (a) which is existing electronic message board standards
- Add new and updated standards for electronic message signs

Section 106-13 – Sign height, area, construction, and placement standards

 Revise (a) Ground signs to change <u>electronic message boards</u> to <u>electronic message signs</u>

WALL SIGNS

Section 106-13 – Sign height, area, construction, and placement standards

- (b) Building signs
- Revise (1) Wall signs to revise second sentence to permit wall signs on three faces of the building instead of two faces: Each structure or tenant space may have wall signage on a maximum of two building faces.
- Revised (1)(b) Maximum area to change the sign area calculation from <u>15 percent of habitable wall</u> area to <u>15 percent of exterior wall area</u>.
- Revised (1)(e) to provide that the wall sign must be located at least 12 inches from the edge of a wall or tenant space, cornice line, parapet wall, apparent flat roofline, or eaves line of the building.