

TEXAS LOCAL GOVERNMENT PURCHASING COOPERATIVE BUYBOARD

Vendor	RUSH TRUCK CENTER	Date Prepared	10/22/2018
Contact for Vendor:	COLTON KRUSE	Phone	(830) 302-5219
End User:	City of North Richland Hills		
End User Contact:	Zane Ryan	Phone/Fax	(817) 427-6384
Product Description:	Peterbilt 337 Chassis		

A: Base Price in Bid/Proposal Number: 521-16		Series: 337 \$ 67,500.00				
B: Published Options(Itemize Below)						
	DESCRIPTION	AMOUNT		OPT #	DESCRIPTION	AMOUNT
Peterbilt	Frame & Equipment	\$ 1,060.00	Peterbilt	Fuel Tanks/Battery Box & Bumper	\$ 10.00	
Peterbilt	Front Axle & Equipment	\$ 62.00	Peterbilt	Cab & Equipment	\$ 2,709.00	
Peterbilt	Rear Axle & Equipment	\$ 1,524.00	Peterbilt	Paint	\$ 442.00	
Peterbilt	Engine & Equipment	\$ 2,679.00	RTC-0051	21 Pt. Rush Care Package	\$ 1,236.00	
Peterbilt	Transmission & Equipment	\$ 10,644.00	RTC-0053	Body Prep Package	\$ 2,438.00	
Peterbilt	Air & Trailer Equipment	\$ 1,136.00	RTC-0126	500E	\$ 121,641.00	
Peterbilt	Tires & Wheels	\$ 877.00				
Subtotal Column 1: \$ 17,982.00			Subtotal Column 2: \$ 128,476.00			
Published Options added to Base Price(Subtotal of "Col 1" & "Col 2")					\$ 146,458.00	

C: Subtotal of A + B		\$ 213,958.00
D: Non Published Options		
Bergkamp FP5 Flameless Patcher with Options	\$ (13,499.00)	
Subtotal Column 1: \$ (13,499.00)		Subtotal Column 2: \$ -

Unpublished Options added to Base price (Subtotal "Col 1 + Col 2") \$ (13,499.00)

E: Contract Price Adjustment (If any, explain here)		
Price Level Increase		\$ 1,077.34

F: Total of C + D +/- E \$ 201,536.34

G: Quantity ordered Units: 1.00 x F \$ 201,536.34

H: BUYBOARD Administrative Fee % \$ 400.00

I: Non-Equipment Charges & Credits (I.e.: Ext. Warranty, Trade-In, Delivery, etc.)		

J: TOTAL PURCHASE PRICE INCLUDING (G+H+I) \$ 201,936.34



PAVEMENT PRESERVATION SOLUTIONS

6

October 11, 2018

City of North Richland Hills, TX

Dear Sir:

REFERENCE PROPOSAL NUMBER PROPOSAL NAME: CONSTRUCTION EQUIPMENT, ROAD AND BRIDGE EQUIPMENT 515-16

DITCHING TRENCHING AND UTILITY EQUIPMENT

PRICE LIST FOR THE FP5 FLAMELESS PATCHER AND OPTIONS

(PATCHER BODY ONLY – MOUNTED ON CUSTOMER’S TRUCK)

PRICING REMAINS IN EFFECT UNTIL NOVEMBER 30, 2018

One Bergkamp FP5 Flameless Patcher as described in attached specs \$73,610.00

InPave Telematics System

Included in this price are the following features:

Hydraulically driven Auger with dual motors

Agitator with hydraulic motor

Spoils bins side and rear

All material tanks on Service Platform, ladder, climb assist handles

Hydraulically operated hopper doors

Compressed Air/Tack System for proper cleaning/tacking of repair area

Back up alarm

Oversized Lockable storage

Standard chute folds into shoveling platform

Conspicuity Marking, Paint Color of Choice

Twin Cleaning Fluid Wands (platform and rear for cleaning tools)

One Year Warranty (Extended warranty options are available)

Available Options

Stanley Model BR67 Pavement Breaker mounted onto hyd lift platform 3,200.00

Wacker Packer Model VP1550AW “ “ “ “: 4,500.00

Single Strobe mounted onto a pedestal LED Lighting 695.00

Ten Light Arrow board LED Lighting 985.00

LED Lighting on machine (Rear hopper lights, tail lights on fenders etc) 1,200.00

Cone Holder 195.00

Back up camera 1,800.00

Swing Auger Attachment 9,667.00

Rear cleaning Fluid Line on retractable reel 905.00

Mounting of unit to include pto and pressure compensated pump 5,450.00

Delivery into State of Texas and training package 2,750.00

Tool holder (mounted onto rear bin) & Tool Holder (mounted onto side bin) 390.00

Swing Arm (Pivot) Tack System 2,795.00

Total \$108,142.00



RTC Dallas MD D551
4200 Irving Blvd

City of N Richland Hills
4301 City Point

Dallas, Texas United States 75247
Phone: (214) 624-9103
Fax:
Email:

N Richland Hills, Texas United States 76180
Phone: (817) 427-6384
Fax:
Contact Email:
Prepared for:

Vehicle Summary

Unit		Chassis	
Model:	Model 337	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs)	23000
Description:	Berkamp Inc Chassis	G.C.W. (lbs):	35000
Application		Road Conditions:	
Intended Serv.:	Utility/Lube Service	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Other Body Type	Wheelbase (in):	199
Length (ft):	24	Overhang (in):	45.8
Height (ft):	13.5	Fr Axle to BOC (in):	69.8
Max Laden Weight (lbs):	1000	Cab to Axle (in):	129.2
		Cab to EOF (in):	175.0
Trailer		Overall Comb. Length (in):	283
No. of Trailer Axles:	0		
Type:		Special Req.	
Length (ft):	0	United States Registry	
Height (ft):	0.0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

PACCAR FINANCIAL	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 10/30/2018 9:30:27 AM
Effective Date: Jul 1, 2018
Prepared by: Administrator

Complete

Model Number: Model 337
Quote/DTPO/CO: Q63055030
Version Number: 37.11



RTC Dallas MD D551
4200 Irving Blvd

City of N Richland Hills
4301 City Point

Dallas, Texas United States 75247
Phone: (214) 624-9103
Fax:
Email:

N Richland Hills, Texas United States 76180
Phone: (817) 427-6384
Fax:
Contact Email:
Prepared for:

Data	Code	Description	\$ List	Weight
Base Model				
0003371	O	Model 337 The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	92,839	10,070
0091200	O	Other Commodity	0	0
0093140	O	Utility/Lube Service Truck used to service construction and mining equipment. Includes bodies such as, mechanics service bodies, tire hoists, fuel/lube, boom, etc.	0	0
0095200	O	Other Body Type	0	0
0098170	O	United States Registry	0	0
Configuration				
0200699	O	Other Secondary Manufacturer (Specify by narrative) N02000 BERGKAMP	0	0
Frame & Equipment				
0515030	S	10-5/8in Steel Rails to 285in 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	129
0612230	O	Custom Wheelbase or Overhang Engineering approval may be required.	365	0
0613090	O	Three-Piece Crossmembers	695	0
0644090	S	EOF Square without Xmbr For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1012130	O	Meritor MFS+12 12,000 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service	0	33

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 10/30/2018 9:30:27 AM
Effective Date: Jul 1, 2018
Prepared by: Administrator

Complete

Model Number: Model 337
Quote/DTPO/CO: Q63055030
Version Number: 37.11



Data	Code	Description	\$ List	Weight
1111190	O	Taper Leaf Springs, Shocks 12,000 lb	38	0
1243040	S	Power Steering Sheppard HD94 For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	O	Power Steering Reservoir Frame Mounted	0	0
1353545	S	PHP10 Aluminum PreSet Hubs	0	0
1380260	S	Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0	0
1391410	O	Gusseted Cam Brackets, Steer Axle	24	0

Rear Axle & Equipment

1513180	O	Dana Spicer S23-190 23,000 lb Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	1,078	344
1616360	S	PHP10 Aluminum PreSet Hubs	0	0
1631310	S	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	0	0
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	24	2
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680950	S	Stability System Not Selected or Not Available	0	0
1681337	S	Single Drive Axle (Model 337)	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1705380	O	Ratio 5.38 Rear Axle	0	0
1816020	O	Reyco 79KB Multi Leaf 23,000 Lb	47	30
1911070	O	Reyco Helper Springs 4,500 lbs For use with Reyco 79KB suspension	375	62

Engine & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 9:30:27 AM	Complete	Model Number:	Model 337
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q63055030
Prepared by:	Administrator		Version Number:	37.11



Data	Code	Description	\$ List	Weight
2074209	S	PACCAR PX-9 260@2200 GOV@2200 720@1300 Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 75...Standard Maximum Speed Limit [LSL] N21330 N207 0....Expiration Distance N21350 P001 64...Maximum Accelerator Pedal Vehicle Speed N21370 P059 64...Maximum Cruise Speed N21400 N203 252..Reserve Speed Function Reset Distance N21410 N202 0....Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0....Reserve Speed Limit Offset N21440 P015 NO...Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 2200.Max PTO Speed N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0....Expiration Distance N21510 P520 YES..Enable Idle Shutdown Park Brake Set N21520 P030 5...Timer Setting N21530 P233 YES..Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning N21550 P516 35...Engine Load Threshold N21570 P031 NO...Idle Shutdown Manual Override N21590 P230 YES..Enable Hot Ambient Automatic Override N21610 P172 40...Low Ambient Temperature Threshold N21620 P173 60...Intermediate Ambient Temperature Threshold N21630 P171 80...High Ambient Temperature Threshold	0	0
2091310	O	Engine Idle Shutdown Timer Disabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372	O	Eff EIST NA Expiration Miles	0	0
2091640	O	Effective VSL Setting NA	0	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed	0	0
2522110	O	PACCAR 12V Starter N/A PACCAR MX Engines	0	0
2535040	O	3 Optima DT31T Batteries 2700 CCA Threaded Stud type terminal. AGM (Absorbent Glass Material). Stranded copper battery cables are double aught (00) or larger to reduce resistance.	783	55
2539030	O	Battery Disconnect Switches (2) Mounted in Cab LH Side of Driver Seat	558	9

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 9:30:27 AM	Complete	Model Number:	Model 337
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q63055030
Prepared by:	Administrator		Version Number:	37.11



Data	Code	Description	\$ List	Weight
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	99	4
2539550	O	Batteries In In-Cab Battery Box	0	0
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops	370	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	O	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	4	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0	0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	O	Exhaust Single RH Side Of Cab DPF/SCR RH Under Cab (2017).	300	29
3381770	O	Curved Tip Standpipe(s)	42	0
3387890	O	36in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	523	4

Transmission & Equipment

4052110	O	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.03)	9,964	195
4210080	S	1710 HD Driveline, 1 Midship Bearing	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 9:30:27 AM	Complete	Model Number:	Model 337
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q63055030
Prepared by:	Administrator		Version Number:	37.11



Data	Code	Description	\$ List	Weight
4233030	O	(1) Dash Mounted Single Acting Air PTO Control Standard with PTO engaged indicator light on Class 8 units. Occupies the space of one gauge. Specing PTO switch does not ensure the PTO will fit.	56	0
4252890	O	Allison FuelSense 2.0 Not Desired	0	0
4252950	O	Omit Allison Neutral At Stop	0	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions	0	0
4256780	O	Allison PTO Enable on Mode Button The PTO function C can be either on a remote wire, or mode button. It depends on the selected input/output package. This function is enabled with the MODE button. Enabling the function alerts the TCM that PTO operation has been requested by the operator. When the function is enabled and all of the required operating conditions exist, the TCM activates Output G: PTO Enable by switching power to wire 130. When this function is enabled, the TCM disables the variable modulated main pressure feature in the transmission, resulting in transmission operation at full main pressure. Required operating conditions for enabling this function are: throttle position is low, engine speed is within Customer Modifiable Constant limits, output speed is within Customer Modifiable Constant limits	0	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison Transmissions.	624	0
Air & Trailer Equipment				
4510320	S	Bendix AD-IS Air Dryer W/Heater And Coalescing Filter	0	0
4520420	O	Pull Cords All Air Tanks	6	0
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543530	O	Clear Outside Frame of All Air System Components LH BOC	501	0
4543540	O	Clear Outside Frame of All Air System Components RH BOC	501	0
4611930	O	Body Connections 5ft BOC Junction Box contains light and power circuits for Body Connections located 5ft from BOC.	134	4
Tires & Wheels				
5066490	O	FF: BR 16Ply 11R22.5 R283A Ecopia	184	-4

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 9:30:27 AM	Complete	Model Number:	Model 337
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q63055030
Prepared by:	Administrator		Version Number:	37.11



Data	Code	Description	\$ List	Weight
5169310	O	RR: BR 16ply 11R22.5 M799 Diameter = 42.0 inches; SLR = 19.5 inches	444	36
5190004	O	Code-rear Tire Qty 04	0	0
5210600	O	FF: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, 2 Hand Holes	83	34
5310600	O	RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	166	68
5390004	O	Code-rear Rim Qty 04	0	0
Fuel Tanks				
5574020	O	45 Gallon Rectangular Fuel Tank LH U/C	180	0
5602045	O	Location LH U/C 45 Gallon	0	0
5652900	O	DEF Tank Mounted LH Under Cab	77	0
5652990	O	Standard DEF To Fuel Ratio 2:1 Or Greater	0	0
5655059	S	DEF Tank Rectangular	0	0
Battery Box & Bumper				
6010390	O	Omit Standard Battery Box Use with passenger seat/in-cab battery box codes only	-247	-45
6040550	S	Aftertreatment RH U/C ALUMINUM Non-Slip Cab Entry Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.	0	0
6121190	O	Steel Styled Aero Bumper Painted Black 2 Tow pins	0	0
Cab & Equipment				
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0	0
6540120	O	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	131	39
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	19	2
6800360	O	Rubber Fender Lips 2 Inch Wide	96	8
6911700	S	Peterbilt UltraRide Driver Seat	0	0
6921700	O	Peterbilt UltraRide Passenger Seat	-163	0
6939070	O	Mounted On In-Cab Battery Box For use with non-air passenger seats only. Includes battery quick disconnect located under driver side door.	853	39
6939400	O	Air Ride Driver	195	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 10/30/2018 9:30:27 AM
Effective Date: Jul 1, 2018
Prepared by: Administrator

Complete

Model Number: Model 337
Quote/DTPO/CO: Q63055030
Version Number: 37.11



Data	Code	Description	\$ List	Weight
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	113	11
7001620	S	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036120	S	Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0	0
7210420	O	Dark Window Tint ipo STD Tint - Day Cab	21	0
7210540	S	Day Cab Rear Window	0	0
7230060	S	One Piece Curved Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7330700	O	Peterbilt Comfort Control - Cab	21	6
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	192	4
7510010	S	Stainless Steel Mirrors 7x16 Right Click on Option to See Picture in Product Portfolio.	0	0
7560850	O	(2) Convex 8 Inch SS Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	240	4
7610020	O	(1) Air Horn 15in Painted Mounted under cab.	172	8
7725710	O	Standard Speaker Package For Cab (2) Speakers	118	4
7725715	O	ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	324	10
7788140	O	Radio Antenna Mounted on LH Mirror Bracket	34	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7900090	O	Triangle Reflector Kit Shipped Loose	17	13
7900270	O	Fire Extinguisher; Cab Mounted Hazmat approved UL listed/rated ABC.	54	8
7901130	O	Backup Alarm (107dB)	53	3

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 10/30/2018 9:30:27 AM **Complete** Model Number: Model 337
Effective Date: Jul 1, 2018 Quote/DTPO/CO: Q63055030
Prepared by: Administrator Version Number: 37.11



Data	Code	Description	\$ List	Weight
8011400	O	Main Transmission Oil Temperature Gauge Located in Driver Information Display	13	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall.	0	0
8071340	O	Bright Bezel Gauges	0	0
8071520	O	(2) Additional Electric Switches Without Wiring	45	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8072560	O	(1) Additional Dash Switch With Wiring Extra wire included at the switch. Availability subject to dash space.	46	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED Light Emitting Diodes	0	0
8133470	O	Switch & Wiring For F/O Beacon/Strobe 10 ft coiled wire BOC/BOS at rear sill	55	2
8133960	O	Daytime Running Lights Required on all Canadian vehicles	60	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup LH/RH Square EOF or Dropped A-Brace	0	0
Paint				
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - 809956EY INGOT SILVER N85400 HOOD TOP 809956EY INGOT SILVER N85500 CAB ROOF 809956EY INGOT SILVER N85200 FRAME L0001EA BLACK N85700 BUMPER L0001EA BLACK N85300 FENDER 809956EY INGOT SILVER	0	0
8531320	O	Axalta Two Stage Effect - Metallic/Pearl Cab/Hood & Sleeper Only	442	0
Options Not Subject To Discount				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 9:30:27 AM	Complete	Model Number:	Model 337
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q63055030
Prepared by:	Administrator		Version Number:	37.11



Data	Code	Description	\$ List	Weight
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9408931	O	PDI At Excellence Peterbilt Location	230	0
Miscellaneous				
9409800	O	2017 EPA Emissions Engine Warranty Only	0	0
9409960	O	Presentation Created Using Featured Spec For Model	0	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)	\$113,988
Freight Charge	\$2,400
Options Not Subject to Discount	\$230
Surcharges Not subject to Discount	\$0
Total Weight	11220

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2018 9:30:27 AM	Complete	Model Number:	Model 337
Effective Date:	Jul 1, 2018		Quote/DTPO/CO:	Q63055030
Prepared by:	Administrator		Version Number:	37.11